

Chemical Compatibility of Nitrile Rubber Products

1 • 1	A MAATING	
	Chemical Tested	Rating
А	Aliphatic Hydrocarbons - Kerosene, Etc.	1
В	Animal & Vegetable Oils	1
С	Aromatic Hydrocarbons - Benzol, Toluol, Etc.	1
D	Bleach	1
E	Concentrated Alkali	1
F	Cutting Oil	1
G	Denatured Alcohol	1
Н	Diesel	1
1	Dilute Alkali	1
J	Engine Oil	1
К	Gasoline	1
L	Hydraulic Fluid Silicate Ester	1
М	Hydraulic Fluid Water Glycol	1
Ν	L.P. Gas, Fuel Oils	1
0	Lubricating Oils - High Aniline	1
Р	Lubricating Oils - Low Aniline Point	1
Q	Mineral Spirits	1
R	Muriatic Acid - 30%, 20 Degrees Baume	1
S	Phosphoric Acid	1
Т	Pine Cleaner	1
U	Refrigerants, Ammonia	1
V	Sodium Hydroxide, Rayon Grade, 25%	1
W	Sulphuric Acid - 30%	1
Х	Transmission Fluid	1
Y	WD40	1
Z	Water	1
AA	Window Cleaner	1
BB	Anti-Freeze	2
CC	Brake Fluid	2
DD	Calcium Hypochlorite - 12%	2
EE	Chlorine Bleach - 12.5%	2
FF	Hydraulic Fluid - Petroleum Base	2
GG	Steam	2
HH	Butyl Alcohol	3
П	Isopropyl Alcohol - 99%	3
JJ	Acetic Acid - 56%	4
KK	Acetone	4
LL	Cyclohexane	4
MM	Refrigerants, Methyl Chloride	4



Comfort Flow



Applies to these products:

Comfort Premier



Comfort Station Max



Hog Heaven



Safety Scrape



DuraComfort



Hog Heaven Tiles



Traction Tread

- 1 = Little or no effect
- 2 = Minor to moderate effect
- 3 = Moderate to severe effect
- 4 = Not recommended