













Chemical Compatibility of Nitrile Rubber Products

	Chemical Tested	Rating	Applies to these products:
A	Aliphatic Hydrocarbons - Kerosene, Etc.	1	 <p>Happy Feet</p>  <p>Hog Heaven III Traffic</p>  <p>Safety Scrape</p>  <p>Hog Heaven</p>  <p>Hog Heaven III Comfort</p>  <p>Cushion Station</p>  <p>Comfort Flow</p>  <p>Comfort Flow HD Modular Tile</p>  <p>Traction Tread</p>  <p>Traction Tread Soft</p>  <p>Hog Heaven Prime</p>  <p>Complete Comfort II</p>
B	Animal & Vegetable Oils	1	
C	Aromatic Hydrocarbons - Benzol, Toluol, Etc.	1	
D	Bleach	1	
E	Concentrated Alkali	1	
F	Cutting Oil	1	
G	Denatured Alcohol	1	
H	Diesel	1	
I	Dilute Alkali	1	
J	Engine Oil	1	
K	Gasoline	1	
L	Hydraulic Fluid Silicate Ester	1	
M	Hydraulic Fluid Water Glycol	1	
N	L.P. Gas, Fuel Oils	1	
O	Lubricating Oils - High Aniline	1	
P	Lubricating Oils - Low Aniline Point	1	
Q	Mineral Spirits	1	
R	Muriatic Acid - 30%, 20 Degrees Baume	1	
S	Phosphoric Acid	1	
T	Pine Cleaner	1	
U	Refrigerants, Ammonia	1	
V	Sodium Hydroxide, Rayon Grade, 25%	1	
W	Sulphuric Acid - 30%	1	
X	Transmission Fluid	1	
Y	WD40	1	
Z	Water	1	
AA	Window Cleaner	1	
BB	Anti-Freeze	2	
CC	Brake Fluid	2	
DD	Calcium Hypochlorite - 12%	2	
EE	Chlorine Bleach - 12.5%	2	
FF	Hydraulic Fluid - Petroleum Base	2	
GG	Steam	2	
HH	Butyl Alcohol	3	
II	Isopropyl Alcohol - 99%	3	
JJ	Acetic Acid - 56%	4	
KK	Acetone	4	
LL	Cyclohexane	4	
MM	Refrigerants, Methyl Chloride	4	

1 = Little or no effect
 2 = Minor to moderate effect
 3 = Moderate to severe effect
 4 = Not recommended